

CLUB Soft Dreams Lux - Wall-to-wall CF - Technical Details

Weight: 2200 g/m²

Material: 100% polyamide

Structure: Tufted cut pile

Backing: Comfort felt

DESCRIPTION	METHOD	DATA
-------------	--------	------

CONSTRUCTION CHARACTERISTICS

Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	5/32
Pile material	Regulation (EU) No 1007/2011	100% polyamide
Coloration	-	Continuous dyed
Backing	ETL	CF - Comfort felt
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	ISO 1765	Apr 16,0 mm.
Tufts	ISO 1763	Apr 48.000 pr.m2
Total carpet weight	ISO 8543	Apr 3.650 g/m2
Pile yarn weight	ETL	2.200 g/m2
Surface pile density	ISO 8543.	Apr 0,150 g/cm3

PERFORMANCE CHARACTERISTICS

Performance areas	ETL	22 - Domestic - General/Medium
Guarantee	ETL	Wear guarantee 5 Years
Static control	ETL	Permanently antistatic
Acou.insu. from impact noise	ETL	35 dB
Acoustical absorption	ETL	0,25 aW
Colour fastness to light	AATCC 16	5.0

SAFETY & ENVIRONMENT

Fire classification	ASTM E-648	Class 1
---------------------	------------	-------------------------

	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 14041	Efl
	BS EN 14041	Efl
CE Labeling	EN 14041	Certified
	Declaration of Performance	DOP E
	Notified body no.	NA
	Ce Year	17
	Content of PCP	DL
	Formaldehyde emission	NA
	Slip resistance	Class DS
Indoor climate	Indoor Air Comfort Gold	Group 7

MANUFACTURER CHARACTERISTICS

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK