

## CLUB Moss - Wall-to-wall WT - Technical Details

Weight: 1750 g/m<sup>2</sup>

Material: Recycled polyamide 6

Structure: Tufted cut pile

Backing: Woven textile

| DESCRIPTION | METHOD | DATA |
|-------------|--------|------|
|-------------|--------|------|

### CONSTRUCTION CHARACTERISTICS

|                        |                              |                                   |
|------------------------|------------------------------|-----------------------------------|
| Structure              | ISO 2424                     | Tufted cut pile                   |
| Gauge                  | ISO 2424                     | 1/8                               |
| Pile material          | Regulation (EU) No 1007/2011 | Recycled polyamide 6              |
| Coloration             | -                            | Continuous dyed                   |
| Backing                | ETL                          | WT - Woven textile                |
| Dimensions             | ISO 3018                     | Approx. 400 cm                    |
| Total thickness        | ISO 1765                     | <a href="#">Apr 11,5 mm.</a>      |
|                        | .                            | 0.45 "                            |
| Surface pile thickness | ISO 1766                     | <a href="#">Apr 9,0 mm.</a>       |
| Tufts                  | ISO 1763                     | <a href="#">Apr 140.900 pr.m2</a> |
| Total carpet weight    | ISO 8543                     | Apr 2.925 g/m2                    |
|                        | .                            | 103.3 oz./yd2                     |
| Pile yarn weight       | ETL                          | 1.750 g/m2                        |
|                        | .                            | 51.63 oz./yd2                     |
| Surface pile density   | ISO 8543.                    | <a href="#">Apr 0,150 g/cm3</a>   |

### PERFORMANCE CHARACTERISTICS

|                          |          |                                                |
|--------------------------|----------|------------------------------------------------|
| Performance areas        | EN 1307  | <a href="#">Class 31 Commercial - Moderate</a> |
| Castor chair suitability | EN 985   | <a href="#">Intensive use</a>                  |
| Static control           | ETL      | Permanently antistatic                         |
| Body walking test        | ISO 6356 | Antistatic                                     |

|                                |             |                            |
|--------------------------------|-------------|----------------------------|
|                                | EN 1815     | Antistatic                 |
| Acou.insu. from impact noise   | ISO 717-2   | <a href="#">31 dB</a>      |
| Acoustical absorption          | ISO 354     | <a href="#">0,25 aW</a>    |
| Thermal insulation             | ETL         | Apr 0,20 m2K/W             |
| Light reflectance              | ETL         | <a href="#">Testreport</a> |
| Colour fastness to light       | ISO 105-B02 | <a href="#">&gt;5</a>      |
| Colour fastness to rubbing wet | ISO 105-X12 | <a href="#">&gt;3</a>      |
| Colour fastness to rubbing dry | ISO 105-X12 | <a href="#">&gt;3-4</a>    |
| Colourfast. to water patterned | ISO 105-E01 | <a href="#">&gt;4</a>      |

## SAFETY & ENVIRONMENT

|                     |                                |                                   |
|---------------------|--------------------------------|-----------------------------------|
| Fire classification | ASTM E-648                     | <a href="#">Class 1</a>           |
|                     | ASTM E662 Smoke Density        | <a href="#">&lt;450</a>           |
|                     | ASTM D2859 Surface Flamm.      | <a href="#">Pass</a>              |
|                     | EN 13501-1 Euroclass           | <a href="#">Cfl-s1</a>            |
| CE Labeling         | EN 14041                       | Certified                         |
|                     | CPR                            | <a href="#">1021-CPR-006-2/16</a> |
|                     | Declaration of Performance     | <a href="#">DOP 1C-PA-WT</a>      |
|                     | Notified body no.              | 1021                              |
|                     | Ce Year                        | 18                                |
|                     | Content of PCP                 | <a href="#">DL</a>                |
|                     | Formaldehyde emission          | <a href="#">NA</a>                |
|                     | Slip resistance                | <a href="#">Class DS</a>          |
| Indoor climate      | Green Label Plus               | <a href="#">Approved</a>          |
|                     | Emissions dans l'air intérieur | A+/A+                             |
|                     | Indoor Air Comfort Gold        | <a href="#">Group 7</a>           |
|                     | ABG                            | ABG-28-02-07-02-2018              |

|             |                             |                                 |
|-------------|-----------------------------|---------------------------------|
| Environment | BASTA                       | Registered                      |
|             | Byggsvarubedömningen ID     | 148287                          |
|             | SundaHus score              | B                               |
|             | BREEAM International        | <a href="#">Approved</a>        |
|             | EPD                         | <a href="#">EPD-IES-0020164</a> |
|             | C2C Certified Full Scope    | Bronze, Version 4.0             |
|             | Recycled Content, ISO 14021 | <a href="#">Apr 4,0 %</a>       |
|             | Recycled Content for LEED   | <a href="#">Apr 4,0 %</a>       |
|             | GWP Cradle to Gate (A1-A3)  | 6,83 KgCO2eq/m2                 |

## MANUFACTURER CHARACTERISTICS

|                       |           |                                               |
|-----------------------|-----------|-----------------------------------------------|
| Factory certification | ISO 9001  | <a href="#">Audited and verified by BVC</a>   |
|                       | ISO 14001 | <a href="#">Audited and verified by BVC</a>   |
|                       | ISO 45001 | <a href="#">Audited and verified by BVC</a>   |
|                       | CRuk      | <a href="#">Member of Carpet Recycling UK</a> |