

COLORTEC/GRAPHIC Entrance Mat - Wall-to-wall LWT - Technical Details

Weight: 1500 g/m²

Material: 80/20 wool and polyamide

Structure: Tufted cut pile

Backing: Laminated woven textile



Class 33 -
Commercial - Heavy



Permanently
antistatic



Certified



Cfl-s1

DESCRIPTION	METHOD	DATA
-------------	--------	------

CONSTRUCTION CHARACTERISTICS

Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/8
Pile material	Regulation (EU) No 1007/2011	80/20 WO/PA & PA monofilament
Coloration	-	Predyed/undyed
Backing	ETL	LWT - Laminated woven textile
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	ISO 1765	Apr 8,5 mm.
Surface pile thickness	ETL	Apr 5,0 mm.
Total carpet weight	ISO 8543	Apr 2.050 g/m2
Pile yarn weight	ETL	1.500 g/m2

PERFORMANCE CHARACTERISTICS

Performance areas	ETL	Class 33 - Commercial - Heavy	
Static control	ETL	Permanently antistatic	

SAFETY & ENVIRONMENT

Fire classification	MER	Certified	
	MER Certificate No.	MERB0001N4A	
	IMO	Certified	

	USCG	164.117/EC0575/MEDB00002R3	
	EC Type-Ex.Cert.No.	MEDB00002R3	
	QS-Cert.of.Assesment-EC No.	MEDD000001V	
	Declaration of Conformity	DOC-MEDB00002R3	
	EN 13501-1 Euroclass	Cfl-s1	
CE Labeling	EN 14041	Certified	
	CPR	1021-CPR-063-2/23	
	Declaration of Performance	DOP 9C - Entrance Mat LWT	
	Notified body no.	1021	
	Ce Year	21	
	Content of PCP	DL	
	Formaldehyde emission	NA	
	Slip resistance	Class DS	
Indoor climate	Indoor Air Comfort Gold	Group 17	

MANUFACTURER CHARACTERISTICS

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK