

**ege**

**Colortec Wool 1300  
LT - Laminated textile**

Productdescription

---





# Colortec Wool 1300 LT - Laminated textile

Productdescription



| DESCRIPTION                         | METHOD   | DATA  |
|-------------------------------------|--|---|
| <b>CONSTRUCTION CHARACTERISTICS</b> |  |   |
| STRUCTURE                           | ISO 2424   | Tufted cut pile   |
| GAUGE                               | ISO 2424   | 1/7   |
| PILE MATERIAL                       | DIR 96/73, 96/74   | 100% wool   |
| COLORATION                          | -  | Predyed/undyed  |
| BACKING                             | ETL  | IMO LT  |
| DIMENSIONS                          | ISO 3018   | Approx. 400/500 cm  |
| TOTAL THICKNESS                     | ISO 1765   | Apr 11,0 mm.  |
| SURFACE PILE THICKNESS              | ETL  | Apr 7,5 mm.   |
| TUFTS                               | ETL  | Apr 103.776 pr.m2   |
| TOTAL CARPET WEIGHT                 | ISO 8543   | Apr 2.125 g/m2  |
| PILE YARN WEIGHT                    | ETL  | 1.300 g/m2  |
| SURFACE PILE WEIGHT                 | ISO 8543.  | Apr 813 g/m2  |
| SURFACE PILE DENSITY                | ISO 8543.  | Apr 0,123 g/cm3   |
| <b>PERFORMANCE CHARACTERISTICS</b>  |  |   |
| PERFORMANCE AREAS                   | EN 1307  | Class 32 Commercial - General   |
| THERMAL INSULATION                  | ETL  | Apr 0,19 m2K/W  |
| COLOUR FASTNESS TO LIGHT            | ISO 105-B02  | >4  |
| COLOUR FASTNESS TO RUBBING WET      | ISO 105-X12  | >3  |
| COLOUR FASTNESS TO RUBBING DRY      | ISO 105-X12  | >3-4  |
| COLOUR FASTNESS TO WATER PLAIN      | ISO 105-E01  | >3-4  |
| <b>SAFETY &amp; ENVIRONMENT</b>     |  |   |
| FIRE CLASSIFICATION                 | IMO<br>USCG<br>EC Type-Ex.Cert.No.<br>QS-Cert.of.Assesment-EC No.<br>Declaration of Conformity<br>ASTM E-648<br>ASTM E662 Smoke Density<br>ASTM D2859 Surface Flamm.<br>EN 13501-1 Euroclass | Certified<br>164.117/EC0575/MEDB00008R2<br>MEDB00008R2<br>MEDD000001V<br>DOC-MEDB00008R2<br>Class 1<br><450<br>Pass<br>Cfl-s1 |
| CE LABELING                         | EN 14041<br>Declaration of Performance<br>Notified body no.<br>Ce Year   | Certified<br>DOP WO-LT<br>NA<br>24  |



# Colortec Wool 1300 LT - Laminated textile

## Productdescription

---

|                               |                             |                     |
|-------------------------------|-----------------------------|---------------------|
| INDOOR CLIMATE<br>ENVIRONMENT | Content of PCP              | DL                  |
|                               | Formaldehyde emission       | NA                  |
|                               | Slip resistance             | Class DS            |
|                               | Indoor Air Comfort Gold     | Group 17            |
|                               | BREEAM International        | Approved            |
|                               | Environmental Product Decl. | MD-25044-EN         |
|                               | C2C Certified Full Scope    | Bronze, Version 4.0 |
|                               | Recycled Content, ISO 14021 | Apr 0,0 %           |
|                               | Recycled Content for LEED   | Apr 0,0 %           |
|                               | GWP Cradle to Gate (A1-A3)  | 12,90 KgCO2eq/m2    |

---

## GUIDES

|                               |    |          |
|-------------------------------|----|----------|
| INSTALLATION + ADHESIVE GUIDE | DK | Dansk    |
|                               | N  | Norsk    |
|                               | S  | Svensk   |
|                               | GB | English  |
|                               | D  | Deutsch  |
|                               | F  | Francais |
| CLEANING, STAIN REMOVAL       | DK | Dansk    |
|                               | N  | Norsk    |
|                               | S  | Svensk   |
|                               | GB | English  |
|                               | D  | Deutsch  |
|                               | F  | Francais |

---

## MANUFACTURER CHARACTERISTICS

|                       |           |                               |
|-----------------------|-----------|-------------------------------|
| FACTORY CERTIFICATION | ISO 9001  | Audited and verified by BVC   |
|                       | ISO 14001 | Audited and verified by BVC   |
|                       | ISO 45001 | Audited and verified by BVC   |
|                       | CRuk      | Member of Carpet Recycling UK |

---



## Colortec Wool 1300 LT - Laminated textile

Productdescription

---



### **Most of our carpets are 100% Cradle to Cradle Bronze Certified®**

**We want to leave the right footprint and make sustainability available to everyone.**

The Cradle to Cradle Certified Product Standard helps us do exactly that and therefore most of our carpets are Cradle to Cradle Certified® Bronze.

With this product certificate, we prove to the world that we do our utmost to keep valuable materials in circulation, cut down on waste and harmful substances, take better care of our scarce resources, sustain the groundwater, reduce CO2 emissions and ensure social fairness in our operations and value chain.

**Cradle to Cradle Certified® is the only choice**

With our carpets, it's easier than ever before to choose sustainably. You can pick your very own favourite from thousands of colours, patterns, structures and qualities and in addition, many of our carpets are Cradle to Cradle Certified® Bronze which means that you can leave the people and planet care taking to us, while focusing your own attention on our great selection of designs.