

## ECO MATTER - Wall-to-wall WT - Technical Details

Weight: 445 g/m<sup>2</sup>

Material: Recycled polyamide 6

Structure: Woven loop pile


Backing: Woven textile



Intensive use



Yes



Class 33 -  
Commercial - Heavy



>3-4

| DESCRIPTION | METHOD | DATA |
|-------------|--------|------|
|-------------|--------|------|

### CONSTRUCTION CHARACTERISTICS

|                     |                              |                             |
|---------------------|------------------------------|-----------------------------|
| Structure           | ISO 2424                     | Woven loop pile             |
| Pile material       | Regulation (EU) No 1007/2011 | Recycled polyamide 6        |
| Coloration          | -                            | Continuous dyed             |
| Backing             | ETL                          | WT - Woven textile          |
| Dimensions          | ISO 3018                     | Approx. 400 cm              |
| Total thickness     | ISO 1765                     | <a href="#">Apr 3,5 mm.</a> |
| Total carpet weight | ISO 8543                     | Apr 2.325 g/m2              |
| Pile yarn weight    | ETL                          | 445 g/m2                    |

### PERFORMANCE CHARACTERISTICS

|                               |                 |                                               |                                                                                       |
|-------------------------------|-----------------|-----------------------------------------------|---------------------------------------------------------------------------------------|
| Performance areas             | EN 1307         | <a href="#">Class 33 - Commercial - Heavy</a> |  |
| TGA                           | TGA Certificate | Nr.TGA.2026/003                               |                                                                                       |
| Castor chair suitability      | EN 985          | <a href="#">Intensive use</a>                 |  |
| Suitability for use on stairs | EN 1963         | <a href="#">Yes</a>                           |  |
| Body walking test             | ISO 6356        | Antistatic                                    |                                                                                       |
| Acou.insu. from impact noise  | ISO 717-2       | 15 dB                                         |                                                                                       |
| Acoustical absorption         | ISO 354         | <a href="#">0,15 aW</a>                       |                                                                                       |
| Light reflectance             | ETL             | <a href="#">Testreport</a>                    |                                                                                       |
| Colour fastness to light      | ISO 105-B02     | <a href="#">&gt;5</a>                         |                                                                                       |

|                                |             |                         |                                                                                     |
|--------------------------------|-------------|-------------------------|-------------------------------------------------------------------------------------|
| Colour fastness to rubbing wet | ISO 105-X12 | <a href="#">&gt;3</a>   |                                                                                     |
| Colour fastness to rubbing dry | ISO 105-X12 | <a href="#">&gt;3-4</a> |  |
| Colour fastness to water plain | ISO 105-E01 | <a href="#">&gt;3-4</a> |                                                                                     |

## SAFETY & ENVIRONMENT

|                     |                             |                                   |
|---------------------|-----------------------------|-----------------------------------|
| Fire classification | EN 13501-1 Euroclass        | Cfl-s1                            |
| CE Labeling         | EN 14041                    | Certified                         |
|                     | CPR                         | <a href="#">1021-CPR-006-2/16</a> |
|                     | Declaration of Performance  | <a href="#">DOP 1C-PA-WT</a>      |
|                     | Ce Year                     | 26                                |
|                     | Content of PCP              | <a href="#">DL</a>                |
|                     | Formaldehyde emission       | <a href="#">NA</a>                |
|                     | Slip resistance             | <a href="#">Class DS</a>          |
| Environment         | BREEAM International        | <a href="#">Approved</a>          |
|                     | EPD                         | <a href="#">EPD-IES-0008855</a>   |
|                     | Recycled Content, ISO 14021 | <a href="#">Apr 19,0 %</a>        |
|                     | Recycled Content for LEED   | <a href="#">Apr 12,0 %</a>        |
|                     | LEED V4                     | <a href="#">Qualified</a>         |
|                     | LEED V5                     | <a href="#">Qualified</a>         |

## MANUFACTURER CHARACTERISTICS

|                       |           |                                               |
|-----------------------|-----------|-----------------------------------------------|
| Factory certification | ISO 9001  | <a href="#">Audited and verified by BVC</a>   |
|                       | ISO 14001 | <a href="#">Audited and verified by BVC</a>   |
|                       | ISO 45001 | <a href="#">Audited and verified by BVC</a>   |
|                       | CRuk      | <a href="#">Member of Carpet Recycling UK</a> |