

## ECO Mineral - Wall-to-wall WT - Technical Details

Weight: 600 g/m<sup>2</sup>

Material: Recycled polyamide 6

Structure: Woven loop pile

Backing: Woven textile

| DESCRIPTION | METHOD | DATA |
|-------------|--------|------|
|-------------|--------|------|

### CONSTRUCTION CHARACTERISTICS

|                     |                              |                             |
|---------------------|------------------------------|-----------------------------|
| Structure           | ISO 2424                     | Woven loop pile             |
| Pile material       | Regulation (EU) No 1007/2011 | Recycled polyamide 6        |
| Coloration          | -                            | Continuous dyed             |
| Backing             | ETL                          | WT - Woven textile          |
| Dimensions          | ISO 3018                     | Approx. 400 cm              |
| Total thickness     | ISO 1765                     | <a href="#">Apr 4,0 mm.</a> |
| Total carpet weight | ISO 8543                     | Apr 2.500 g/m2              |
| Pile yarn weight    | ETL                          | 600 g/m2                    |
|                     | .                            | 17,7 oz./yd2                |

### PERFORMANCE CHARACTERISTICS

|                               |              |                                               |
|-------------------------------|--------------|-----------------------------------------------|
| Performance areas             | EN 1307      | <a href="#">Class 33 - Commercial - Heavy</a> |
| Castor chair suitability      | EN 985       | <a href="#">Intensive use</a>                 |
| Suitability for use on stairs | EN ISO 12951 | <a href="#">Yes</a>                           |
| Static control                | ETL          | Permanently antistatic                        |
| Body walking test             | ISO 6356     | Antistatic                                    |
| Acou.insu. from impact noise  | ISO 717-2    | <a href="#">17 dB</a>                         |
| Acoustical absorption         | ISO 354      | <a href="#">0,15 aW</a>                       |
| Thermal insulation            | ETL          | Apr 0,07 m2K/W                                |
| Light reflectance             | ETL          | <a href="#">Testreport</a>                    |
| Colour fastness to light      | ISO 105-B02  | <a href="#">&gt;5</a>                         |

|                                |             |                         |
|--------------------------------|-------------|-------------------------|
|                                | AATCC 16    | <a href="#">5.0</a>     |
| Colour fastness to rubbing wet | ISO 105-X12 | <a href="#">&gt;3</a>   |
| Colour fastness to rubbing dry | ISO 105-X12 | <a href="#">&gt;3-4</a> |
| Colour fastness to water plain | ISO 105-E01 | <a href="#">&gt;3-4</a> |

## SAFETY & ENVIRONMENT

|                     |                             |                                     |
|---------------------|-----------------------------|-------------------------------------|
| Fire classification | EN 13501-1 Euroclass        | <a href="#">Cfl-s1</a>              |
| CE Labeling         | EN 14041                    | Certified                           |
|                     | CPR                         | <a href="#">1021-CPR-006-2/16</a>   |
|                     | Declaration of Performance  | <a href="#">DOP 1C-PA-WT</a>        |
|                     | Notified body no.           | 1021                                |
|                     | Ce Year                     | 22                                  |
|                     | Content of PCP              | <a href="#">DL</a>                  |
|                     | Formaldehyde emission       | <a href="#">NA</a>                  |
|                     | Slip resistance             | <a href="#">Class DS</a>            |
| Indoor climate      | Green Label Plus            | <a href="#">Approved</a>            |
|                     | Indoor Air Comfort Gold     | <a href="#">Group 14</a>            |
| Environment         | Byggsvarubedömningen ID     | 164040                              |
|                     | BREEAM International        | <a href="#">Approved</a>            |
|                     | EPD                         | <a href="#">MD-24054-EN</a>         |
|                     | C2C Certified Full Scope    | <a href="#">Bronze, Version 4.0</a> |
|                     | Recycled Content, ISO 14021 | <a href="#">Apr 24,0 %</a>          |
|                     | Recycled Content for LEED   | <a href="#">Apr 18,0 %</a>          |
|                     | GWP Cradle to Gate (A1-A3)  | 6,18 KgCO2eq/m2                     |

## MANUFACTURER CHARACTERISTICS

|                       |           |                                             |
|-----------------------|-----------|---------------------------------------------|
| Factory certification | ISO 9001  | <a href="#">Audited and verified by BVC</a> |
|                       | ISO 14001 | <a href="#">Audited and verified by BVC</a> |

|           |                                               |
|-----------|-----------------------------------------------|
| ISO 45001 | <a href="#">Audited and verified by BVC</a>   |
| CRuk      | <a href="#">Member of Carpet Recycling UK</a> |