

## EPOCA Tempo Stripe - Wall-to-wall WT - Technical Details

Weight: 500 g/m<sup>2</sup>

Material: Recycled polyamide 6

Structure: Tufted loop pile

Backing: Woven textile

| DESCRIPTION | METHOD | DATA |
|-------------|--------|------|
|-------------|--------|------|

### CONSTRUCTION CHARACTERISTICS

|                        |                              |                      |
|------------------------|------------------------------|----------------------|
| Structure              | ISO 2424                     | Tufted loop pile     |
| Gauge                  | ISO 2424                     | 1/10                 |
| Pile material          | Regulation (EU) No 1007/2011 | Recycled polyamide 6 |
| Coloration             | -                            | Solution dyed        |
| Backing                | ETL                          | WT - Woven textile   |
| Dimensions             | ISO 3018                     | Approx. 400 cm       |
| Total thickness        | ETL                          | Apr 5,5 mm.          |
|                        | .                            | 0.28 "               |
| Surface pile thickness | ETL                          | Apr 2,5 mm.          |
| Total carpet weight    | ISO 8543                     | Apr 2.200 g/m2       |
|                        | .                            | 64.9 oz./yd2         |
| Pile yarn weight       | ETL                          | 500 g/m2             |
|                        | .                            | 14.75 oz./yd2        |

### PERFORMANCE CHARACTERISTICS

|                               |           |                               |
|-------------------------------|-----------|-------------------------------|
| Performance areas             | EN 1307   | Class 33 - Commercial - Heavy |
| Castor chair suitability      | ETL       | Intensive use                 |
| Suitability for use on stairs | ETL       | Yes                           |
| Static control                | ETL       | Permanently antistatic        |
| Acou.insu. from impact noise  | ISO 717-2 | <a href="#">24 dB</a>         |
| Acoustical absorption         | ISO 354   | <a href="#">0,20 aW</a>       |

|                          |          |                            |
|--------------------------|----------|----------------------------|
| Thermal insulation       | ETL      | Apr 0,09 m2K/W             |
| Light reflectance        | ETL      | <a href="#">Testreport</a> |
| Colour fastness to light | AATCC 16 | <a href="#">5.0</a>        |

## SAFETY & ENVIRONMENT

|                     |                            |                                     |
|---------------------|----------------------------|-------------------------------------|
| Fire classification | ASTM E-648                 | <a href="#">Class 1</a>             |
|                     | ASTM E662 Smoke Density    | <a href="#">&lt;450</a>             |
|                     | ASTM D2859 Surface Flamm.  | <a href="#">Pass</a>                |
|                     | EN 13501-1 Euroclass       | <a href="#">Bfl-s1</a>              |
| CE Labeling         | EN 14041                   | Certified                           |
|                     | CPR                        | <a href="#">1021-CPR-006-1/16</a>   |
|                     | Declaration of Performance | <a href="#">DOP 1B-PA-WT</a>        |
|                     | Notified body no.          | 1021                                |
|                     | Ce Year                    | 12                                  |
|                     | Content of PCP             | <a href="#">DL</a>                  |
|                     | Formaldehyde emission      | <a href="#">NA</a>                  |
|                     | Slip resistance            | <a href="#">Class DS</a>            |
| Indoor climate      | Green Label Plus           | <a href="#">Approved</a>            |
|                     | Indoor Air Comfort Gold    | <a href="#">Group 3</a>             |
|                     | ABG                        | ABG-28-01-03-03-2018                |
| Environment         | BASTA                      | Registered                          |
|                     | Byggvarubedömningen ID     | 146841 (WTA)                        |
|                     | SundaHus score             | B (WTA)                             |
|                     | BREEAM International       | <a href="#">Approved</a>            |
|                     | EPD                        | <a href="#">EPD-IES-0009105</a>     |
|                     | C2C Certified Full Scope   | <a href="#">Bronze, Version 4.0</a> |
|                     | GWP Cradle to Gate (A1-A3) | 4,44 KgCO2eq/m2                     |

**MANUFACTURER CHARACTERISTICS**

|                       |           |                                               |
|-----------------------|-----------|-----------------------------------------------|
| Factory certification | ISO 9001  | <a href="#">Audited and verified by BVC</a>   |
|                       | ISO 14001 | <a href="#">Audited and verified by BVC</a>   |
|                       | ISO 45001 | <a href="#">Audited and verified by BVC</a>   |
|                       | CRuk      | <a href="#">Member of Carpet Recycling UK</a> |