

ege

**Epoca Texture 2000
WT - Woven textile**

Productdescription





Epoca Texture 2000 WT - Woven textile

Productdescription



DESCRIPTION	METHOD	DATA
CONSTRUCTION CHARACTERISTICS		
STRUCTURE	ISO 2424	Tufted cut pile
GAUGE	ISO 2424	1/8
PILE MATERIAL	DIR 96/73, 96/74	Regenerated and regenerable PA
COLORATION	-	Continuous dyed
BACKING	ETL	WT -Woven textile
DIMENSIONS	ISO 3018	Approx. 400 cm
TOTAL THICKNESS	ISO 1765	Apr 15,5 mm. 0.61"
SURFACE PILE THICKNESS	ISO 1766	Apr 13,0 mm.
TUFTS	ISO 1763	Apr 196.000 pr.m2
TOTAL CARPET WEIGHT	ISO 8543	Apr 3.550 g/m2 104.73 oz./yd2
PILE YARN WEIGHT	ETL	2.000 g/m2 59 oz./yd2
SURFACE PILE DENSITY	ISO 8543.	Apr 0,140 g/cm3

PERFORMANCE CHARACTERISTICS		
PERFORMANCE AREAS	EN 1307	Class 33 - Commercial - Heavy
	Gulvbranchen	Class 33
STATIC CONTROL	ETL	Permanently antistatic
BODY WALKING TEST	ISO 6356	Antistatic
ACOU.INSU. FROM IMPACT NOISE	ISO 717-2	36 dB
ACOUSTICAL ABSORPTION	ISO 354	0,30 aW
THERMAL INSULATION	ETL	Apr 0,27 m2K/W
LIGHT REFLECTANCE	ETL	Testreport
COLOUR FASTNESS TO LIGHT	ISO 105-B02	>5
	AATCC 16	4.0
COLOUR FASTNESS TO RUBBING WET	ISO 105-X12	>3
	AATCC 165	5.0
COLOUR FASTNESS TO RUBBING DRY	ISO 105-X12	>3-4
	AATCC 165	5.0
COLOUR FASTNESS TO WATER PLAIN	ISO 105-E01	>3-4
CLEANING	AATCC 138	5.0
COLOUR FAST.OXIDES OF NITROGEN	AATCC 164	3.5
OTHER PERFORMANCE TESTS	ASTM D5252 Hexapod	4.0/ 3.5
	-	Commercial - Heavy
	AATCC 134 Electrost.propensity	2,9 kV



Epoca Texture 2000 WT - Woven textile

Productdescription

SAFETY & ENVIRONMENT

FIRE CLASSIFICATION	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Cfl-s1
CE LABELING	ASISO 9239.1-2003	3,30 KW/m2
	EN 14041	Certified
	CPR	1021-CPR-006-2/16
	Declaration of Performance	DOP 1C-PA-WT
	Notified body no.	1021
	Ce Year	12
	Content of PCP	DL
	Formaldehyde emission	NA
INDOOR CLIMATE	Slip resistance	Class DS
	Green Label Plus	Approved
	Emissions dans l'air intérieur	A+/A+
	Indoor Air Comfort Gold	Group 7
	ABG	ABG-28-02-07-01-2018
ENVIRONMENT	BASTA	Registered
	Byggvarubedömningen ID	148293
	SundaHus score	B
	BREEAM International	Approved
	Environmental Product Decl.	EPD-IES-0020165
	C2C Certified Full Scope	Bronze, Version 4.0
	Recycled Content, ISO 14021	Apr 3,0 %
	Recycled Content for LEED	Apr 3,0 %
	LEED	Qualified
	GWP Cradle to Gate (A1-A3)	7,74 KgCO2eq/m2

GUIDES

INSTALLATION + ADHESIVE GUIDE	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
CLEANING, STAIN REMOVAL	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

MANUFACTURER CHARACTERISTICS



Epoca Texture 2000 WT - Woven textile

Productdescription

FACTORY CERTIFICATION

ISO 9001
ISO 14001
ISO 45001
CRuk

Audited and verified by BVC
Audited and verified by BVC
Audited and verified by BVC
Member of Carpet Recycling UK



Epoca Texture 2000 WT - Woven textile

Productdescription



Most of our carpets are 100% Cradle to Cradle Bronze Certified®

We want to leave the right footprint and make sustainability available to everyone.

The Cradle to Cradle Certified Product Standard helps us do exactly that and therefore most of our carpets are Cradle to Cradle Certified® Bronze.

With this product certificate, we prove to the world that we do our utmost to keep valuable materials in circulation, cut down on waste and harmful substances, take better care of our scarce resources, sustain the groundwater, reduce CO2 emissions and ensure social fairness in our operations and value chain.

Cradle to Cradle Certified® is the only choice

With our carpets, it's easier than ever before to choose sustainably. You can pick your very own favourite from thousands of colours, patterns, structures and qualities and in addition, many of our carpets are Cradle to Cradle Certified® Bronze which means that you can leave the people and planet care taking to us, while focusing your own attention on our great selection of designs.