

**ege**

**Graphic 80/20 1300  
LF - Laminated felt**

Productdescription

---






# Graphic 80/20 1300

## LF - Laminated felt

Productdescription



| DESCRIPTION                         | METHOD           | DATA                    |
|-------------------------------------|------------------|-------------------------|
| <b>CONSTRUCTION CHARACTERISTICS</b> |                  |                         |
| STRUCTURE                           | ISO 2424         | Tufted cut pile         |
| GAUGE                               | ISO 2424         | 1/8                     |
| PILE MATERIAL                       | DIR 96/73, 96/74 | 80% wool, 20% polyamide |
| COLORATION                          | -                | Predyed/undyed          |
| BACKING                             | ETL              | LF - Laminated felt     |
| DIMENSIONS                          | ISO 3018         | Approx. 400/500 cm      |
| TOTAL THICKNESS                     | ISO 1765         | Apr 11,5 mm.            |
| SURFACE PILE THICKNESS              | ETL              | Apr 6,0 mm.             |
| TUFTS                               | ISO 1763         | Apr 123.700 pr.m2       |
| TOTAL CARPET WEIGHT                 | ISO 8543         | Apr 2.350 g/m2          |
| PILE YARN WEIGHT                    | ETL              | 1.300 g/m2              |
| SURFACE PILE WEIGHT                 | ISO 8543.        | Apr 825 g/m2            |
| SURFACE PILE DENSITY                | ISO 8543.        | Apr 0,125 g/cm3         |

|                                    |             |                               |
|------------------------------------|-------------|-------------------------------|
| <b>PERFORMANCE CHARACTERISTICS</b> |             |                               |
| PERFORMANCE AREAS                  | EN 1307     | Class 33 - Commercial - Heavy |
| SUITABILITY FOR USE ON STAIRS      | ETL         | Yes                           |
| ACOU.INSU. FROM IMPACT NOISE       | ISO 717-2   | 44 dB                         |
| ACOUSTICAL ABSORPTION              | ISO 354     | 0,35 aW                       |
| THERMAL INSULATION                 | ETL         | Apr 0,20 m2K/W                |
| COLOUR FASTNESS TO LIGHT           | ISO 105-B02 | >4                            |
|                                    | AATCC 16    | 5.0                           |
| COLOUR FASTNESS TO RUBBING WET     | ISO 105-X12 | >3                            |
| COLOUR FASTNESS TO RUBBING DRY     | ISO 105-X12 | >3-4                          |
| COLOURFAST. TO WATER PATTERNED     | ISO 105-E01 | >2-3                          |
| COLOUR FASTNESS TO WATER PLAIN     | ISO 105-E01 | >3-4                          |

|                                 |                           |                            |
|---------------------------------|---------------------------|----------------------------|
| <b>SAFETY &amp; ENVIRONMENT</b> |                           |                            |
| FIRE CLASSIFICATION             | MER                       | Certified                  |
|                                 | MER Certificate No.       | MERB00007XH                |
|                                 | IMO                       | Certified                  |
|                                 | USCG                      | 164.117/EC0575/MEDB00007XH |
|                                 | EC Type-Ex.Cert.No.       | MEDB00007XH                |
|                                 | Declaration of Conformity | DOC-MEDB00007XH            |
|                                 | ASTM E-648                | Class 1                    |
|                                 | ASTM E662 Smoke Density   | <450                       |



## Graphic 80/20 1300 LF - Laminated felt

### Productdescription

---

|                            |                             |                     |
|----------------------------|-----------------------------|---------------------|
| CE LABELING                | ASTM D2859 Surface Flamm.   | Pass                |
|                            | EN 13501-1 Euroclass        | Bfl-s1              |
|                            | EN 14041                    | Certified           |
|                            | CPR                         | 1021-CPR-086-1/22   |
|                            | Declaration of Performance  | DOP 7B-WOPA-LF      |
|                            | Notified body no.           | 1021                |
|                            | Ce Year                     | 07                  |
|                            | Content of PCP              | DL                  |
|                            | Formaldehyde emission       | NA                  |
|                            | Slip resistance             | Class DS            |
| INDOOR CLIMATE             | Green Label Plus            | Approved            |
|                            | Indoor Air Comfort Gold     | Group 17            |
| ENVIRONMENT                | Byggvarudeklaration         | eBVD                |
|                            | Byggvarubedömningen ID      | 141158              |
|                            | SundaHus score              | B                   |
|                            | BREEAM International        | Approved            |
|                            | BREEAM International        | Approved            |
|                            | BREEAM-NOR                  | Approved            |
|                            | Environmental Product Decl. | md-24193-en         |
|                            | C2C Certified Full Scope    | Bronze, Version 4.0 |
|                            | Recycled Content, ISO 14021 | Apr 21,0 %          |
|                            | Recycled Content for LEED   | Apr 16,0 %          |
| GWP Cradle to Gate (A1-A3) | 15,90 KgCO2eq/m2            |                     |

---

### GUIDES

|                               |    |          |
|-------------------------------|----|----------|
| INSTALLATION + ADHESIVE GUIDE | DK | Dansk    |
|                               | N  | Norsk    |
|                               | S  | Svensk   |
|                               | GB | English  |
|                               | D  | Deutsch  |
|                               | F  | Francais |
| CLEANING, STAIN REMOVAL       | DK | Dansk    |
|                               | N  | Norsk    |
|                               | S  | Svensk   |
|                               | GB | English  |
|                               | D  | Deutsch  |
|                               | F  | Francais |

---

### MANUFACTURER CHARACTERISTICS

|                       |           |                               |
|-----------------------|-----------|-------------------------------|
| FACTORY CERTIFICATION | ISO 9001  | Audited and verified by BVC   |
|                       | ISO 14001 | Audited and verified by BVC   |
|                       | ISO 45001 | Audited and verified by BVC   |
|                       | CRuk      | Member of Carpet Recycling UK |

---



## Graphic 80/20 1300 LF - Laminated felt

Productdescription

---



### **Most of our carpets are 100% Cradle to Cradle Bronze Certified®**

**We want to leave the right footprint and make sustainability available to everyone.**

The Cradle to Cradle Certified Product Standard helps us do exactly that and therefore most of our carpets are Cradle to Cradle Certified® Bronze.

With this product certificate, we prove to the world that we do our utmost to keep valuable materials in circulation, cut down on waste and harmful substances, take better care of our scarce resources, sustain the groundwater, reduce CO2 emissions and ensure social fairness in our operations and value chain.

**Cradle to Cradle Certified® is the only choice**

With our carpets, it's easier than ever before to choose sustainably. You can pick your very own favourite from thousands of colours, patterns, structures and qualities and in addition, many of our carpets are Cradle to Cradle Certified® Bronze which means that you can leave the people and planet care taking to us, while focusing your own attention on our great selection of designs.