

ege

Graphic 80/20 1800
LWT - Laminated woven textile

Productdescription






Graphic 80/20 1800

LWT - Laminated woven textile

Productdescription



DESCRIPTION	METHOD	DATA
CONSTRUCTION CHARACTERISTICS		
STRUCTURE	ISO 2424	Tufted cut pile
GAUGE	ISO 2424	1/8
PILE MATERIAL	DIR 96/73, 96/74	80% wool, 20% polyamide
COLORATION	-	Predyed/undyed
BACKING	ETL	LWT - Laminated woven textile
DIMENSIONS	ISO 3018	Approx. 400/500 cm
TOTAL THICKNESS	ISO 1765	Apr 8,0 mm.
SURFACE PILE THICKNESS	ETL	Apr 6,0 mm.
TUFTS	ISO 1763	Apr 187.700 pr.m2
TOTAL CARPET WEIGHT	ISO 8543	Apr 2.450 g/m2
PILE YARN WEIGHT	ETL	1.800 g/m2
SURFACE PILE WEIGHT	ISO 8543.	Apr 1.249 g/m2
SURFACE PILE DENSITY	ISO 8543.	Apr 0,195 g/cm3
PERFORMANCE CHARACTERISTICS		
PERFORMANCE AREAS	EN 1307	Class 33 - Commercial - Heavy
SUITABILITY FOR USE ON STAIRS	ETL	Yes
ACOU.INSU. FROM IMPACT NOISE	ISO 717-2	37 dB
ACOUSTICAL ABSORPTION	ISO 354	0,20 aW
THERMAL INSULATION	ETL	Apr 0,14 m2K/W
COLOUR FASTNESS TO LIGHT	ISO 105-B02	>4
	AATCC 16	5.0
COLOUR FASTNESS TO RUBBING WET	ISO 105-X12	>3
COLOUR FASTNESS TO RUBBING DRY	ISO 105-X12	>3-4
COLOURFAST. TO WATER PATTERNED	ISO 105-E01	>2-3
COLOUR FASTNESS TO WATER PLAIN	ISO 105-E01	>3-4
SAFETY & ENVIRONMENT		
FIRE CLASSIFICATION	MER	Certified
	MER Certificate No.	MERB000017X
	IMO	Certified
	USCG	164.117/EC0575/MEDB000017X
	EC Type-Ex.Cert.No.	MEDB000017X
	Declaration of Conformity	DOC-MEDB000017X
	EN 13501-1 Euroclass	Bfl-s1
CE LABELING	EN 14041	Certified



Graphic 80/20 1800 LWT - Laminated woven textile

Productdescription

	CPR	1021-CPR-085-1/22
	Declaration of Performance	DOP 6B-WOPA-LWT
	Notified body no.	1021
	Ce Year	07
	Content of PCP	DL
	Formaldehyde emission	NA
INDOOR CLIMATE	Slip resistance	Class DS
	Green Label Plus	Approved
	Indoor Air Comfort Gold	Group 17
ENVIRONMENT	Byggarubedömningen ID	150473
	SundaHus score	B
	BREEAM International	Approved
	BREEAM International	Approved
	BREEAM-NOR	Approved
	Environmental Product Decl.	md-24195-en
	C2C Certified Full Scope	Bronze, Version 4.0
	Recycled Content, ISO 14021	Apr 0,0 %
	Recycled Content for LEED	Apr 0,0 %
	GWP Cradle to Gate (A1-A3)	17,60 KgCO2eq/m2

GUIDES

INSTALLATION + ADHESIVE GUIDE	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
CLEANING, STAIN REMOVAL	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

MANUFACTURER CHARACTERISTICS

FACTORY CERTIFICATION	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK



Graphic 80/20 1800 LWT - Laminated woven textile

Productdescription



Most of our carpets are 100% Cradle to Cradle Bronze Certified®

We want to leave the right footprint and make sustainability available to everyone.

The Cradle to Cradle Certified Product Standard helps us do exactly that and therefore most of our carpets are Cradle to Cradle Certified® Bronze.

With this product certificate, we prove to the world that we do our utmost to keep valuable materials in circulation, cut down on waste and harmful substances, take better care of our scarce resources, sustain the groundwater, reduce CO2 emissions and ensure social fairness in our operations and value chain.

Cradle to Cradle Certified® is the only choice

With our carpets, it's easier than ever before to choose sustainably. You can pick your very own favourite from thousands of colours, patterns, structures and qualities and in addition, many of our carpets are Cradle to Cradle Certified® Bronze which means that you can leave the people and planet care taking to us, while focusing your own attention on our great selection of designs.