

ege

Graphic Wool 1300
LWT - Laminated woven textile

Productdescription



Graphic Wool 1300

LWT - Laminated woven textile

Productdescription



| DESCRIPTION | METHOD | DATA |
|-------------------------------------|----------------------------|-------------------------------|
| CONSTRUCTION CHARACTERISTICS | | |
| STRUCTURE | ISO 2424 | Tufted cut pile |
| GAUGE | ISO 2424 | 1/8 |
| PILE MATERIAL | DIR 96/73, 96/74 | 100% wool |
| COLORATION | - | Predyed/undyed |
| BACKING | ETL | LWT - Laminated woven textile |
| DIMENSIONS | ISO 3018 | Approx. 400/500 cm |
| TOTAL THICKNESS | ISO 1765 | Apr 8,0 mm. |
| SURFACE PILE THICKNESS | ETL | Apr 6,0 mm. |
| TUFTS | ISO 1763 | Apr 135.700 pr.m2 |
| TOTAL CARPET WEIGHT | ISO 8543 | Apr 1.950 g/m2 |
| PILE YARN WEIGHT | ETL | 1.300 g/m2 |
| SURFACE PILE DENSITY | ISO 8543. | Apr 0,138 g/cm3 |
| PERFORMANCE CHARACTERISTICS | | |
| PERFORMANCE AREAS | EN 1307 | Class 33 - Commercial - Heavy |
| THERMAL INSULATION | ETL | Apr 0,14 m2K/W |
| COLOUR FASTNESS TO LIGHT | ISO 105-B02 | >4 |
| COLOUR FASTNESS TO RUBBING WET | ISO 105-X12 | >3 |
| COLOUR FASTNESS TO RUBBING DRY | ISO 105-X12 | >3-4 |
| COLOUR FASTNESS TO WATER PLAIN | ISO 105-E01 | >3-4 |
| SAFETY & ENVIRONMENT | | |
| FIRE CLASSIFICATION | ASTM E-648 | Class 1 |
| | ASTM E662 Smoke Density | <450 |
| | ASTM D2859 Surface Flamm. | Pass |
| | EN 13501-1 Euroclass | Cfl-s1 |
| CE LABELING | EN 14041 | Certified |
| | CPR | 1021-CPR-060-2/23 |
| | Declaration of Performance | DOP 4C - WO-LWT |
| | Notified body no. | 1021 |
| | Ce Year | 23 |
| | Content of PCP | DL |
| | Formaldehyde emission | NA |
| | Slip resistance | Class DS |
| INDOOR CLIMATE | Indoor Air Comfort Gold | Group 17 |
| ENVIRONMENT | BREEAM International | Approved |



Graphic Wool 1300

LWT - Laminated woven textile

Productdescription

| | |
|-----------------------------|---------------------|
| Environmental Product Decl. | MD-25046-EN |
| C2C Certified Full Scope | Bronze, Version 4.0 |
| Recycled Content, ISO 14021 | Apr 0,0 % |
| Recycled Content for LEED | Apr 0,0 % |
| GWP Cradle to Gate (A1-A3) | 12,50 KgCO2eq/m2 |

GUIDES

| | | |
|-------------------------------|----|----------|
| INSTALLATION + ADHESIVE GUIDE | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |
| CLEANING, STAIN REMOVAL | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |

MANUFACTURER CHARACTERISTICS

| | | |
|-----------------------|-----------|-------------------------------|
| FACTORY CERTIFICATION | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | ISO 45001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |



Graphic Wool 1300 LWT - Laminated woven textile

Productdescription



Most of our carpets are 100% Cradle to Cradle Bronze Certified®

We want to leave the right footprint and make sustainability available to everyone.

The Cradle to Cradle Certified Product Standard helps us do exactly that and therefore most of our carpets are Cradle to Cradle Certified® Bronze.

With this product certificate, we prove to the world that we do our utmost to keep valuable materials in circulation, cut down on waste and harmful substances, take better care of our scarce resources, sustain the groundwater, reduce CO2 emissions and ensure social fairness in our operations and value chain.

Cradle to Cradle Certified® is the only choice

With our carpets, it's easier than ever before to choose sustainably. You can pick your very own favourite from thousands of colours, patterns, structures and qualities and in addition, many of our carpets are Cradle to Cradle Certified® Bronze which means that you can leave the people and planet care taking to us, while focusing your own attention on our great selection of designs.