

**ege**

**Highline 630**  
**AB - Acoustic backing**

Productdescription

---





# Highline 630

## AB - Acoustic backing

Productdescription



DESCRIPTION	METHOD	DATA
<b>CONSTRUCTION CHARACTERISTICS</b>		
STRUCTURE	ISO 2424	Tufted cut pile
GAUGE	ISO 2424	1/10
PILE MATERIAL	DIR 96/73, 96/74	Regenerated and regenerable PA
COLORATION	-	Millitron dyed
BACKING	ETL	AB - Acoustic backing
DIMENSIONS	ISO 3018	Approx. 400 cm
TOTAL THICKNESS	ISO 1765	Apr 8,5 mm. 0.34"
SURFACE PILE THICKNESS	ISO 1766	Apr 4,0 mm.
TUFTS	ISO 1763	Apr 239.000 pr.m2
TOTAL CARPET WEIGHT	ISO 8543	Apr 2.300 g/m2 67.9 oz./yd2
PILE YARN WEIGHT	ETL	630 g/m2 18.59 oz./yd2
SURFACE PILE DENSITY	ISO 8543.	Apr 0,110 g/cm3

<b>PERFORMANCE CHARACTERISTICS</b>		
PERFORMANCE AREAS	EN 1307	Class 32 Commercial - General
SUITABILITY FOR USE ON STAIRS	EN 1963	Yes
STATIC CONTROL	ETL	Permanently antistatic
BODY WALKING TEST	EN 1815	Antistatic
ACOU.INSU. FROM IMPACT NOISE	ISO 717-2	35 dB
ACOUSTICAL ABSORPTION	ISO 354	0,35 aW
THERMAL INSULATION	ETL	Apr 0,15 m2K/W
LIGHT REFLECTANCE	ETL	Testreport
COLOUR FASTNESS TO LIGHT	ISO 105-B02 AATCC 16	7 4.0
COLOUR FASTNESS TO RUBBING WET	ISO 105-X12	5
COLOUR FASTNESS TO RUBBING DRY	ISO 105-X12	4-5
COLOURFAST. TO WATER PATTERNED	ISO 105-E01	4-5

<b>SAFETY &amp; ENVIRONMENT</b>		
FIRE CLASSIFICATION	MER MER Certificate No. IMO USCG	Certified MERB00002ZR Certified 164.117/EC0575/MEDB00002ZR



## Highline 630 AB - Acoustic backing

### Productdescription

---

	EC Type-Ex.Cert.No.	MEDB00002ZR
	QS-Cert.of.Assesment-EC No.	MEDD000001V
	Declaration of Conformity	DOC-MEDB00002ZR
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Bfl-s1
CE LABELING	EN 14041	Certified
	CPR	1021-CPR-008-1/16
	Declaration of Performance	DOP 3B-PA-AB
	Notified body no.	1021
	Ce Year	07
	Content of PCP	DL
	Formaldehyde emission	NA
	Slip resistance	Class DS
INDOOR CLIMATE	Green Label Plus	Approved
	METS Report	Pass
	Indoor Air Comfort Gold	Group 3
	ABG	ABG-28-01-03-02-2018
ENVIRONMENT	BASTA	Registered
	Byggvarubedömningen ID	146681 (ABA)
	SundaHus score	B (ABA)
	BREEAM International	Approved
	BREEAM-NOR	Approved
	Environmental Product Decl.	EPD-IES-0019436
	C2C Certified Full Scope	Bronze, Version 4.0
	Recycled Content, ISO 14021	Apr 17,0 %
	Recycled Content for LEED	Apr 11,0 %
	LEED	Qualified
	GWP Cradle to Gate (A1-A3)	4,78 KgCO2eq/m2

---

### GUIDES

INSTALLATION + ADHESIVE GUIDE	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
CLEANING, STAIN REMOVAL	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

---

### MANUFACTURER CHARACTERISTICS

---



## Highline 630 AB - Acoustic backing

Productdescription

---

FACTORY CERTIFICATION

ISO 9001  
ISO 14001  
ISO 45001  
CRuk

Audited and verified by BVC  
Audited and verified by BVC  
Audited and verified by BVC  
Member of Carpet Recycling UK

---

**ege**

**Highline 630**

**AB - Acoustic backing**

Productdescription

---



### **Most of our carpets are 100% Cradle to Cradle Bronze Certified®**

**We want to leave the right footprint and make sustainability available to everyone.**

The Cradle to Cradle Certified Product Standard helps us do exactly that and therefore most of our carpets are Cradle to Cradle Certified® Bronze.

With this product certificate, we prove to the world that we do our utmost to keep valuable materials in circulation, cut down on waste and harmful substances, take better care of our scarce resources, sustain the groundwater, reduce CO2 emissions and ensure social fairness in our operations and value chain.

**Cradle to Cradle Certified® is the only choice**

With our carpets, it's easier than ever before to choose sustainably. You can pick your very own favourite from thousands of colours, patterns, structures and qualities and in addition, many of our carpets are Cradle to Cradle Certified® Bronze which means that you can leave the people and planet care taking to us, while focusing your own attention on our great selection of designs.