

**ege**

**Highline 750  
WT - Woven textile**

Productdescription

---





# Highline 750 WT - Woven textile

Productdescription



DESCRIPTION	METHOD	DATA
<b>CONSTRUCTION CHARACTERISTICS</b>		
STRUCTURE	ISO 2424	Tufted cut pile
GAUGE	ISO 2424	1/10
PILE MATERIAL	DIR 96/73, 96/74	Regenerated and regenerable PA
COLORATION	-	Millitron dyed
BACKING	ETL	WT -Woven textile
DIMENSIONS	ISO 3018	Approx. 400 cm
TOTAL THICKNESS	ISO 1765	Apr 7,5 mm.
SURFACE PILE THICKNESS	ISO 1766	Apr 5,0 mm.
TUFTS	ISO 1763	Apr 191.800 pr.m2
TOTAL CARPET WEIGHT	ISO 8543	Apr 2.150 g/m2
PILE YARN WEIGHT	ETL	750 g/m2
		22.13 oz./yd2
SURFACE PILE DENSITY	ISO 8543.	Apr 0,120 g/cm3
<b>PERFORMANCE CHARACTERISTICS</b>		
PERFORMANCE AREAS	EN 1307	Class 33 - Commercial - Heavy
CASTOR CHAIR SUITABILITY	EN 985	Intensive use
SUITABILITY FOR USE ON STAIRS	EN 1963	Yes
STATIC CONTROL	ETL	Permanently antistatic
BODY WALKING TEST	ISO 6356	Antistatic
ACOU.INSU. FROM IMPACT NOISE	ISO 717-2	26 dB
ACOUSTICAL ABSORPTION	ISO 354	0,20 aW
THERMAL INSULATION	ETL	Apr 0,13 m2K/W
LIGHT REFLECTANCE	ETL	Testreport
COLOUR FASTNESS TO LIGHT	ISO 105-B02	>5
	AATCC 16	3.5
COLOUR FASTNESS TO RUBBING WET	ISO 105-X12	>3
COLOUR FASTNESS TO RUBBING DRY	ISO 105-X12	>3-4
COLOURFAST. TO WATER PATTERNED	ISO 105-E01	>4
<b>SAFETY &amp; ENVIRONMENT</b>		
FIRE CLASSIFICATION	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Bfl-s1
CE LABELING	EN 14041	Certified



## Highline 750 WT - Woven textile

### Productdescription

---

	CPR	1021-CPR-006-1/16
	Declaration of Performance	DOP 1B-PA-WT
	Ce Year	20
	Content of PCP	DL
	Formaldehyde emission	NA
INDOOR CLIMATE	Slip resistance	Class DS
	Green Label Plus	Approved
	METS Report	Pass
	Indoor Air Comfort Gold	Group 3
ENVIRONMENT	ABG	ABG-28-01-03-01-2018
	BASTA	Registered
	Byggvarubedömningen ID	146651 (WTA)
	SundaHus score	B (WTA)
	BREEAM International	Approved
	BREEAM-NOR	Approved
	Environmental Product Decl.	EPD-IES-0019437
	C2C Certified Full Scope	Bronze, Version 4.0
	Recycled Content, ISO 14021	Apr 35,0 %
	Recycled Content for LEED	Apr 26,0 %
	ECOproductNorway	Approved
	LEED	Qualified
	GWP Cradle to Gate (A1-A3)	5,37 KgCO2eq/m2

---

### GUIDES

INSTALLATION + ADHESIVE GUIDE	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
CLEANING, STAIN REMOVAL	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

---

### MANUFACTURER CHARACTERISTICS

FACTORY CERTIFICATION	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

---

**ege**

## **Highline 750 WT - Woven textile**

Productdescription

---



### **Most of our carpets are 100% Cradle to Cradle Bronze Certified®**

**We want to leave the right footprint and make sustainability available to everyone.**

The Cradle to Cradle Certified Product Standard helps us do exactly that and therefore most of our carpets are Cradle to Cradle Certified® Bronze.

With this product certificate, we prove to the world that we do our utmost to keep valuable materials in circulation, cut down on waste and harmful substances, take better care of our scarce resources, sustain the groundwater, reduce CO2 emissions and ensure social fairness in our operations and value chain.

**Cradle to Cradle Certified® is the only choice**

With our carpets, it's easier than ever before to choose sustainably. You can pick your very own favourite from thousands of colours, patterns, structures and qualities and in addition, many of our carpets are Cradle to Cradle Certified® Bronze which means that you can leave the people and planet care taking to us, while focusing your own attention on our great selection of designs.