

ege

**Highline Loop
WT - Woven textile**

Productdescription





DESCRIPTION	METHOD	DATA
CONSTRUCTION CHARACTERISTICS		
STRUCTURE	ISO 2424	Tufted loop pile
GAUGE	ISO 2424	1/10
PILE MATERIAL	DIR 96/73, 96/74	Regenerated and regenerable PA
COLORATION	-	Millitron dyed
BACKING	ETL	WT -Woven textile
DIMENSIONS	ISO 3018	Approx. 400 cm
TOTAL THICKNESS	ISO 1765	Apr 7,0 mm. 0.28"
SURFACE PILE THICKNESS	ISO 1766	Apr 4,0 mm.
TUFTS	ISO 1763	Apr 153.000 pr.m2
TOTAL CARPET WEIGHT	ISO 8543	Apr 2.200 g/m2 64.9 oz./yd2
PILE YARN WEIGHT	ETL	680 g/m2 20.06 oz./yd2
SURFACE PILE DENSITY	ISO 8543.	Apr 0,115 g/cm3

PERFORMANCE CHARACTERISTICS		
PERFORMANCE AREAS	EN 1307 Gulvbranchen	Class 33 - Commercial - Heavy Class 33
CASTOR CHAIR SUITABILITY	EN 985	Intensive use
SUITABILITY FOR USE ON STAIRS	EN 1963	Yes
STATIC CONTROL	ETL	Permanently antistatic
BODY WALKING TEST	EN 1815	Antistatic
ACOU.INSU. FROM IMPACT NOISE	ISO 717-2	27 dB
ACOUSTICAL ABSORPTION	ISO 354 Sound absorbtion class	0,20 aW E
THERMAL INSULATION	ETL	Apr 0,12 m2K/W
LIGHT REFLECTANCE	ETL	Testreport
COLOUR FASTNESS TO LIGHT	ISO 105-B02 AATCC 16	>5 3.5
COLOUR FASTNESS TO RUBBING WET	ISO 105-X12 AATCC 165	>3 5.0
COLOUR FASTNESS TO RUBBING DRY	ISO 105-X12 AATCC 165	>3-4 5.0
COLOURFAST. TO WATER PATTERNED	ISO 105-E01	>4
CLEANING	AATCC 138	5.0
COLOUR FAST.OXIDES OF NITROGEN	AATCC 164	5.0
OTHER PERFORMANCE TESTS	ASTM D5252 Hexapod -	3.5/3.0 Commercial - Heavy



Highline Loop WT - Woven textile

Productdescription

AATCC 134 Electrostatic propensity 0.6 kV

SAFETY & ENVIRONMENT

FIRE CLASSIFICATION	BS 6853, NF X 70-100	Approved	
	ASTM E-648	Class 1	
	ASTM E662 Smoke Density	<450	
	ASTM D2859 Surface Flamm.	Pass	
	EN 13501-1 Euroclass	Cfl-s1	
	HU,MSZ 14800-9:1985	Suitable	
	ASISO 9239.1-2003	10,20 KW/m2	
	CE LABELING	EN 14041	Certified
		CPR	1021-CPR-006-2/16
		Declaration of Performance	DOP 1C-PA-WT
Notified body no.		1021	
Ce Year		07	
Content of PCP		DL	
Formaldehyde emission		NA	
INDOOR CLIMATE	Slip resistance	Class DS	
	INSTA 800	Dust level 5	
	Green Label Plus	Approved	
	METS Report	Pass	
	Emissions dans l'air intérieur	A+/A+	
	Indoor Air Comfort Gold	Group 3	
ENVIRONMENT	ABG	ABG-28-01-03-01-2018	
	BASTA	Registered	
	Byggvarubedömningen ID	142520 (WTA)	
	SundaHus score	B (WTA)	
	BREEAM International	Approved	
	BREEAM-NOR	Approved	
	Environmental Product Decl.	MD-21080-EN	
	C2C Certified Full Scope	Bronze, Version 4.0	
	Recycled Content, ISO 14021	Apr 35,0 %	
	Recycled Content for LEED	Apr 28,0 %	
	ECOproductNorway	Approved	
	LEED	Qualified	
	GWP Cradle to Gate (A1-A3)	5,40 KgCO2eq/m2	

GUIDES

INSTALLATION + ADHESIVE GUIDE	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
CLEANING, STAIN REMOVAL	DK	Dansk
	N	Norsk



Highline Loop WT - Woven textile

Productdescription

S	Svensk
GB	English
D	Deutsch
F	Francais

MANUFACTURER CHARACTERISTICS

FACTORY CERTIFICATION	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

ege

Highline Loop WT - Woven textile

Productdescription



Most of our carpets are 100% Cradle to Cradle Bronze Certified®

We want to leave the right footprint and make sustainability available to everyone.

The Cradle to Cradle Certified Product Standard helps us do exactly that and therefore most of our carpets are Cradle to Cradle Certified® Bronze.

With this product certificate, we prove to the world that we do our utmost to keep valuable materials in circulation, cut down on waste and harmful substances, take better care of our scarce resources, sustain the groundwater, reduce CO2 emissions and ensure social fairness in our operations and value chain.

Cradle to Cradle Certified® is the only choice

With our carpets, it's easier than ever before to choose sustainably. You can pick your very own favourite from thousands of colours, patterns, structures and qualities and in addition, many of our carpets are Cradle to Cradle Certified® Bronze which means that you can leave the people and planet care taking to us, while focusing your own attention on our great selection of designs.