

ege

Highline 80/20 1100
WT - Woven textile

Productdescription





| DESCRIPTION | METHOD | DATA |
|-------------------------------------|-----------------------------|---|
| CONSTRUCTION CHARACTERISTICS | | |
| STRUCTURE | ISO 2424 | Tufted cut pile |
| GAUGE | ISO 2424 | 1/8 |
| PILE MATERIAL | DIR 96/73, 96/74 | 80% wool, 20% polyamide |
| COLORATION | - | Millitron dyed |
| BACKING | ETL | WT -Woven textile |
| DIMENSIONS | ISO 3018 | Approx. 400 cm |
| TOTAL THICKNESS | ISO 1765 | Apr 8,0 mm. 0.32" |
| SURFACE PILE THICKNESS | ISO 1766 | Apr 5,5 mm. |
| TUFTS | ISO 1763 | Apr 120.000 pr.m2 |
| TOTAL CARPET WEIGHT | ISO 8543 | Apr 2.600 g/m2 76.7 oz./yd2 |
| PILE YARN WEIGHT | ETL | 1.100 g/m2 32.45 oz./yd2 |
| SURFACE PILE DENSITY | ISO 8543. | Apr 0,150 g/cm3 |
| BIOCIDAL TREATMENT | Biocidal Product Regulation | Contains preservative to control microbiological deterioration |

| | | |
|------------------------------------|------------------------------------|-------------------------------|
| PERFORMANCE CHARACTERISTICS | | |
| PERFORMANCE AREAS | EN 1307 | Class 32 Commercial - General |
| STATIC CONTROL | ETL | Permanently antistatic |
| BODY WALKING TEST | EN 1815 | Antistatic |
| ACOU.INSU. FROM IMPACT NOISE | ISO 717-2 | 30 dB |
| ACOUSTICAL ABSORPTION | ISO 354 | 0,20 aW |
| THERMAL INSULATION | ETL | Apr 0,14 m2K/W |
| LIGHT REFLECTANCE | ETL | Testreport |
| COLOUR FASTNESS TO LIGHT | ISO 105-B02 | >4 |
| | AATCC 16 | 4.5 |
| COLOUR FASTNESS TO RUBBING WET | ISO 105-X12 | >3 |
| | AATCC 165 | 5.0 |
| COLOUR FASTNESS TO RUBBING DRY | ISO 105-X12 | >3-4 |
| | AATCC 165 | 5.0 |
| COLOURFAST. TO WATER PATTERNED | ISO 105-E01 | >4 |
| CLEANING | AATCC 138 | 4.0 |
| COLOUR FAST.OXIDES OF NITROGEN | AATCC 164 | 5.0 |
| OTHER PERFORMANCE TESTS | ASTM D5252 Hexapod | 2.5/ 2.0 |
| | - | Commercial -General |
| | AATCC 134 Electrostatic propensity | 2.7 kV |



Highline 80/20 1100 WT - Woven textile

Productdescription

SAFETY & ENVIRONMENT

| | | |
|---------------------|--------------------------------|-----------------------|
| FIRE CLASSIFICATION | BS 6853, NF X 70-100 | Approved |
| | IMO | Certified with PES WT |
| | Russian Maritime reg. Shipping | Product complies |
| | ASTM E-648 | Class 1 |
| | ASTM E662 Smoke Density | <450 |
| | ASTM D2859 Surface Flamm. | Pass |
| | Polen std. | OK |
| | EN 13501-1 Euroclass | Cfl-s1 |
| | Transport Canada | Suitable |
| | HU,MSZ 14800-9:1985 | Suitable |
| | RUSSIA | Approved |
| | EN 14041 | Certified |
| | CPR | 1021-CPR-012-2/16 |
| CE LABELING | Declaration of Performance | DOP 1C-WO/PA-WT |
| | Notified body no. | 1021 |
| | Ce Year | 07 |
| | Content of PCP | DL |
| | Formaldehyde emission | NA |
| | Slip resistance | Class DS |
| | POLEN | Approved |
| INDOOR CLIMATE | Green Label Plus | Approved |
| | DCL Attestation of Conformity | Product complies |
| | METS Report | Pass |
| | Emissions dans l'air intérieur | A+/A+ |
| | Indoor Air Comfort Gold | Group 4 |
| | ABG | ABG-28-01-04-01-2018 |
| | BASTA | Registered |
| ENVIRONMENT | Byggvarubedömningen ID | 148797 |
| | SundaHus score | B |
| | BREEAM International | Approved |
| | BREEAM-NOR | Approved |
| | Environmental Product Decl. | MD-21077-EN |
| | C2C Certified Full Scope | Bronze, Version 4.0 |
| | Recycled Content, ISO 14021 | Apr 4,0 % |
| | Recycled Content for LEED | Apr 4,0 % |
| | LEED | Qualified |
| | GWP Cradle to Gate (A1-A3) | 13,80 KgCO2eq/m2 |

GUIDES

| | | |
|-------------------------------|----|----------|
| INSTALLATION + ADHESIVE GUIDE | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |
| CLEANING, STAIN REMOVAL | DK | Dansk |



Highline 80/20 1100 WT - Woven textile

Productdescription

| | |
|----|----------|
| N | Norsk |
| S | Svensk |
| GB | English |
| D | Deutsch |
| F | Francais |

MANUFACTURER CHARACTERISTICS

| | | |
|-----------------------|-----------|-------------------------------|
| FACTORY CERTIFICATION | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | ISO 45001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |

ege

**Highline 80/20 1100
WT - Woven textile**

Productdescription



Most of our carpets are 100% Cradle to Cradle Bronze Certified®

We want to leave the right footprint and make sustainability available to everyone.

The Cradle to Cradle Certified Product Standard helps us do exactly that and therefore most of our carpets are Cradle to Cradle Certified® Bronze.

With this product certificate, we prove to the world that we do our utmost to keep valuable materials in circulation, cut down on waste and harmful substances, take better care of our scarce resources, sustain the groundwater, reduce CO2 emissions and ensure social fairness in our operations and value chain.

Cradle to Cradle Certified® is the only choice

With our carpets, it's easier than ever before to choose sustainably. You can pick your very own favourite from thousands of colours, patterns, structures and qualities and in addition, many of our carpets are Cradle to Cradle Certified® Bronze which means that you can leave the people and planet care taking to us, while focusing your own attention on our great selection of designs.